



FDK44

CARATTERISTICHE

- Alta capacità di asciugatura
- Robusta struttura in metallo
- Controllo elettronico
- Ore di funzionamento
- Molto silenzioso
- Plug and play
- Display digitale per la regolazione dell'umidità
- Riavvio automatico dopo un'interruzione di corrente
- Filtro aria lavabile
- Basso consumo elettrico



FDK100

CARATTERISTICHE	UNITA'	FDK44	FDK100
PORTATA D'ARIA	m3/h	450	1100
CAPACITÀ A 30°C / 80%	l/h	36/24	80/24
REFRIGERANTE	-	R410a	R410a
CAMPO DI LAVORO	C°	1-35	1-35
ALIMENTAZIONE ELETTRICA	V/Ph/Hz	230/1/50	230/1/50
TIPO DI CONNESSIONE	-	SCHUKO	SCHUKO
MAX. POTENZA ASSORBITA	W	570	1050
MAX. CORRENTE ASSORBITA	A	3.9	7.2
RUMOROSITA'	dB	51	56
SCARICO DIRETTO ACQUA	-	SI	SI
DIMENSIONI	mm	350X420X580	516X516X656
PESO	Kg	34	48



FDK44

CHARACTERISTICS

- High drying capacity
- Sturdy metal construction
- Electronic control
- Hours of operation
- Very quiet
- Plug and play
- Digital display for humidity regulation
- Automatic restart after power failure
- Washable air filter
- Low power consumption



FDK100

CHARACTERISTICS	UNIT'	FDK44	FDK100
AIR FLOW	m3/h	450	1100
CAPACITY AT 30°C / 80%	l/h	36/24	80/24
REFRIGERATOR	-	R410a	R410a
WORK CAMP	C°	1-35	1-35
POWER SUPPLY	V/Ph/Hz	230/1/50	230/1/50
CONNECTION TYPE	-	SCHUKO	SCHUKO
MAX. POWER ABSORBED	IN	570	1050
MAX. CURRENT ABSORBED	A	3.9	7.2
NOISE	dB	51	56
DIRECT WATER DISCHARGE	-	YES	YES
DIMENSIONS	mm	350X420X580	516X516X656
WEIGHT	Kg	34	48