

MIZAR PX

GENERATORI D'ARIA CALDA A GASOLIO DIRETTI DIRECT DIESEL OIL HEATERS



- Struttura metallica verniciata a polveri epossidiche
- Caldaia di combustione in acciaio Inox
- Controllo fiamma elettronico con fotoresistenza
- Post-ventilazione per raffreddamento camera di combustione
- Termostato di sicurezza per sovratemperatura
- Modello 15 portatile
- Modelli 20-30-40-50 carrellati
- Idoneo per ambienti aperti o semiaperti
- Predisposto per termostato ambiente
- Pompa gasolio ad ingranaggi

- Metal structure painted with epoxy powders
- Stainless steel combustion chamber
- Electronic flame check with photo-resistance
- Post-ventilation for combustion chamber cooling
- Safety thermostat for over-temperature
- Model 15 portable
- Models 20-30-40-50 trolley-mounted
- Suitable for open or semi-open environments
- Pre-set for ambient thermostat
- Gear oil pump

MIZAR	⚡			🌬️ air outlet	⚡ absorbed power	🗣️ power supply	🍷 fuel consumption	🚰 tank capacity	📦 mm (LxPxH)	📦 weight	📦 pallet	📦 dimensions mm (LxPxH)
	Kw	Kcal/h	BTU/h									
15 PX	16,5	14.280	56.299	500 m³/h	150 watt	1-230/50 ph-volt/Hz	1,40 kg/h	20 l	800x310 x530	22,8 kg	16 pz.	1200x800 x2230
20 PX	20	17.200	68.242	500 m³/h	150 watt	1-230/50 ph-volt/Hz	1,65 kg/h	20 l	800x310 x530	26,3 kg	16 pz.	1200x800 x2230
30 PX	30	25.800	102.362	1.750 m³/h	150 watt	1-230/50 ph-volt/Hz	2,53 kg/h	35 l	1125x450 x620	48 kg	6 pz.	1200x900 x2000
40 PX	40	34.400	136.483	1.750 m³/h	150 watt	1-230/50 ph-volt/Hz	3,37 kg/h	35 l	1125x450 x620	48 kg	6 pz.	1200x900 x2000
50 PX	50	43.000	170.604	1.750 m³/h	200 watt	1-230/50 ph-volt/Hz	4,22 kg/h	35 l	1125x450 x620	48 kg	6 pz.	1200x900 x2000

