



AX 10
AX 15
AX 21

CARATTERISTICHE

- L'**AX10/15/21** hanno una resistente struttura interamente in metallo garantendo prestazioni ad alta velocità.
- L'inclinazione regolabile di 180° consente un controllo preciso del flusso d'aria.
- Le ruote in gomma ad alta resistenza e la maniglia di facile presa garantiscono una mobilità fluida.
- Le robuste pale in alluminio garantiscono un flusso d'aria potente e duraturo con una manutenzione minima.
- Ideali per officine, garage, fabbriche e altri ambienti industriali impegnativi.

CARATTERISTICHE	UNITA'	AX10	AX15	AX 21
PORTATA D'ARIA- VELOCITA' MAX	m3/h	9.900	17.100	21.600
PORTATA D'ARIA VELOCITA' MEDIA	m3/h	8.550	15.600	19.920
PORTATA D'ARIA VELOCITA' MINIMA	m3/h	7.200	13.500	17.400
ALIMENTAZIONE ELETTRICA	v/Hz	220/240/50	220/240/50	220/240/50
POTENZA ASSORBITA - VELOCITA' MAX	W	180	315	630
CORRENTE ASSORBITA - VELOCITA' MAX	Amp	1.7	3	4
DIMENSIONI	mm	700x700x300	910x935x350	1090x380x1130
DIMENSIONI VENTOLA	mm	600	750	900
PESO	Kg	10	24.5	33



AX 10
AX 15
AX 21

CHARACTERISTICS

- The **AX10/15/21** feature a robust, all-metal structure ensuring high-speed performance.
- The adjustable 180° tilt allows precise control of airflow.
- Heavy-duty rubber wheels and an easy-grip handle ensure smooth mobility.
- The durable aluminium fan blades provide powerful and long-lasting airflow with minimal maintenance.
- Ideal for workshops, garages, factories, and other demanding industrial environments.

TECHNICAL SPECIFICATIONS	UNIT	AX10	AX15	AX 21
AIRFLOW – MAX. SPEED	m3/h	9.900	17.100	21.600
AIRFLOW – AVERAGE SPEED	m3/h	8.550	15.600	19.920
AIRFLOW – MINIMUM SPEED	m3/h	7.200	13.500	17.400
POWER SUPPLY	v/Hz	220/240/50	220/240/50	220/240/50
POWER INPUT – MAX. SPEED	W	180	315	630
CURRENT INPUT – MAX. SPEED	Amp	1.7	3	4
DIMENSIONS	mm	700x700x300	910x935x350	1090x380x1130
DIMENSIONS FAN	mm	600	750	900
WEIGHT	Kg	10	24.5	33