



**CX50
CX200**



CARATTERISTICHE

- Elevato flusso d'aria con basso assorbimento di corrente
- Leggero e facile da trasportare
- Base antiscivolo stabile
- Resistente per uso professionale
- Comode maniglie
- Struttura resistente agli urti
- Silenzioso
- È adatto per asciugare all'aria pavimenti e tappeti
- La grande girante della ventola genera un flusso d'aria maggiore per una maggiore efficienza
- Ventilazione migliorata della struttura
- Polipropilene ad alta densità per una maggiore durata

CARATTERISTICHE	UNITA'	CX50	CX200
PORTATA D'ARIA - MAX VELOCITA'	m3/h	576	2.040
VELOCITA'	-	1	2
ALIMENTAZIONE ELETTRICA	V/Hz	220-240/50	220-240/50
POTENZA	W	70	450
DIMENSIONI VENTOLA	Ø mm	145X160	240X200
DIMENSIONI	mm	300x275x310	400x380x460
PESO	Kg	5	11.5



**CX50
CX200**



CHARACTERISTICS

- High airflow with low current draw
- Lightweight and easy to transport
- Stable non-slip base
- Durable for professional use
- Convenient handles
- Impact-resistant structure
- Quiet operation
- Suitable for air-drying floors and carpets
- Large fan impeller generates higher airflow for increased efficiency
- Improved ventilation of the structure
- High-density polypropylene for extended durability

TECHNICAL SPECIFICATIONS	UNIT	CX50	CX200
AIRFLOW – MAX. SPEED	m3/h	576	2.040
SPEED	-	1	2
POWER SUPPLY	V/Hz	220-240/50	220-240/50
POWER	W	70	450
FAN DIMENSIONS	Ø mm	145X160	240X200
DIMENSIONS	mm	300x275x310	400x380x460
WEIGHT	Kg	5	11.5