



ITM K2 CG 300 E
ITM K2 CG 400 E
ITM K2 CG 600 E

CARATTERISTICHE

- Struttura metallica verniciata a polveri epossidiche
- Bruciatore in acciaio Inox
- Scatola comandi in materiale termoplastico con grado di isolamento IP44
- Controlli di sicurezza sulla fiamma effettuati tramite termocopia, termostato ed elettrovalvola
- Accensione piezoelettrica
- Motore con protezione termica
- Idoneo per ambienti aperti e semiaperti

CARATTERISTICHE	UNITA'	ITM K2 CG 300 E	ITM K2 CG 400 E	ITM K2 CG 600 E
POTENZA TERMICA	kW Kcal/H btu/H	23.35 - 37.3 20.081 - 32.078 79.672 - 127.271	30.7 - 46.5 26.400 - 40.000 104.751 - 158.662	46-69 40.000 - 60.000 156.956 - 235.434
PORTATA D'ARIA	m3/H	1000	1.600	3.270
POTENZA ASSORBITA	Watt	80	103	188
ALIMENTAZIONE ELETTRICA	ph-volt/Hz	1-230/50	1-230/50	1-230/50
CONSUMO CARBURANTE	Kg/h	1.5 - 2.90	2.37 - 3.55	3.55 -5.40
PRESSIONE CARBURANTE	bar/psi	1.5 - 21.75	1.5 - 21.75	1.5 - 21.75
TIPO DI CARBURANTE	-	G30 PROPANO BUTANO	G30 PROPANO BUTANO	G30 PROPANO BUTANO
DIMENSIONI	mm	600X260X420	690X340X540	690X340X540
PESO	Kg	9.5	17.5	18.5



ITM K2 CG 300 E
ITM K2 CG 400 E
ITM K2 CG 600 E

CHARACTERISTICS

- Metal structure painted with epoxy powders
- Stainless steel burner
- Control box in thermoplastic material with IP44 insulation rating
- Flame safety checks performed via thermocouple, thermostat and solenoid valve
- Piezoelectric ignition
- Motor with thermal protection
- Suitable for open and semi-open spaces

TECHNICAL SPECIFICATIONS	UNIT	ITM K2 CG 300 E	ITM K2 CG 400 E	ITM K2 CG 600 E
THERMAL OUTPUT	kW Kcal/H btu/H	23.35 - 37.3 20.081 - 32.078 79.672 - 127.271	30.7 - 46.5 26.400 - 40.000 104.751 - 158.662	46-69 40.000 - 60.000 156.956 - 235.434
AIRFLOW	m3/H	1000	1.600	3.270
POWER INPUT	Watt	80	103	188
POWER SUPPLY	ph-volt/Hz	1-230/50	1-230/50	1-230/50
FUEL CONSUMPTION	Kg/h	1.5 - 2.90	2.37 - 3.55	3.55 -5.40
FUEL PRESSURE	bar/psi	1.5 - 21.75	1.5 - 21.75	1.5 - 21.75
FUEL TYPE	-	G30 PROPANE BUTANE	G30 PROPANE BUTANE	G30 PROPANE BUTANE
DIMENSIONS	mm	600X260X420	690X340X540	690X340X540
WEIGHT	Kg	9.5	17.5	18.5