



ITM K2 CG 300 M
ITM K2 CG 400 M
ITM K2 CG 600 M

CARATTERISTICHE

- Struttura metallica verniciata a polveri epossidiche
- Bruciatore in acciaio Inox
- Scatola comandi in materiale termoplastico con grado di isolamento IP44
- Controlli di sicurezza sulla fiamma effettuati tramite termocopia, termostato ed elettrovalvola
- Accensione piezoelettrica
- Motore con protezione termica
- Idoneo per ambienti aperti e semiaperti

CARATTERISTICHE	UNITA'	ITM K2 CG 300 M	ITM K2 CG 400 M	ITM K2 CG 600 M
POTENZA TERMICA	kW Kcal/H btu/H	23.3-37.3 20.081-32.078 79.672-127.271	30.7-46.5 26.400-40.000 104.751-158.662	46-69 40.000-60.000 156.956-235.434
PORTATA D'ARIA	m ³ /H	1.000	1.600	3.270
POTENZA ASSORBITA	Watt	80	103	188
ALIMENTAZIONE ELETTRICA	ph-volt/Hz	1-230/50	1-230/50	1-230/50
CONSUMO CARBURANTE	Kg/h	1.81-2.90	2.00-3.5	3.55-5.40
PRESSIONE CARBURANTE	bar/psi	1.5-21-75	1.5-21-75	1.5-21-75
TIPO DI CARBURANTE	-	G30-31 PROPANO BUTANO	G30-31 PROPANO BUTANO	G30-31 PROPANO BUTANO
DIMENSIONI	mm	600X260X420	690X340X540	590X340X540
PESO	Kg	9.5	17.5	18.5



ITM K2 CG 300 M
ITM K2 CG 400 M
ITM K2 CG 600 M

CHARACTERISTICS

- Metal structure painted with epoxy powders
- Stainless steel burner
- Control box in thermoplastic material with IP44 insulation rating
- Flame safety checks performed via thermocouple, thermostat and solenoid valve
- Piezoelectric ignition
- Motor with thermal protection
- Suitable for open and semi-open spaces

TECHNICAL SPECIFICATIONS	UNIT	ITM K2 CG 300 M	ITM K2 CG 400 M	ITM K2 CG 600 M
THERMAL OUTPUT	kW Kcal/H btu/H	23.3-37.3 20.081-32.078 79.672-127.271	30.7-46.5 26.400-40.000 104.751-158.662	46-69 40.000-60.000 156.956-235.434
AIRFLOW	m3/H	1.000	1.600	3.270
POWER INPUT	Watt	80	103	188
POWER SUPPLY	ph-volt/Hz	1-230/50	1-230/50	1-230/50
FUEL CONSUMPTION	Kg/h	1.81-2.90	2.00-3.5	3.55-5.40
FUEL PRESSURE	bar/psi	1.5-21-75	1.5-21-75	1.5-21-75
FUEL TYPE	-	G30-31 PROPANE BUTANE	G30-31 PROPANE BUTANE	G30-31 PROPANE BUTANE
DIMENSIONS	mm	600X260X420	690X340X540	590X340X540
WEIGHT	Kg	9.5	17.5	18.5